

JINGHAN SWITCH ELECTRONIC CO.,LTD

Attn: Mr John

Tel: +86-574-83067530

Mobile: +86-15867263600

Add: #102 65Building Dongying Xincun Ningbo City Zhejiang Province China

Fax: +86-574-87972399

E-mail: sales@jhswitch.com

Website: <http://www.jhswitch.com>

JINGHAN ROCKER SWITCH KCD1-101BL Series Datasheet



项目 Item	参数 Parameter
额定电流、电压 Rated voltage Rated current	3A 250V AC 6A 125V AC
绝缘电阻 Insulated resistance	≥ 100M Ω
接触电阻 Contact resistance	≤ 50m Ω
介电强度(极间) Dielectric strength	1500VAC/5S
电器寿命 Endurance	≥ 10000 Cycles
使用温度 Ambient temperature	T 85

系列号
Series No

KCD1-101BL

电路图
Circuit diagram

端子规格
Terminal

开关标记
Making

1	空白	No Making
2	○ —	
3		●
4	⊕	⊖
5	○	
6	⊥	⊥
7	客人要求	

颜色代码
Color code

K	黑
W	白
Y	黄
R	红
G	绿
O	橙
B	蓝

Electronics specification	Expansion	British Called	American Called	Description	Symbol
SPST	Single pole, single throw	One-way	Two-way	A simple on-off switch. The two terminals are either connected together or disconnected from each other. An example is a light switch.	

JINGHAN SWITCH ELECTRONIC CO.,LTD

Attn: Mr John

Tel: +86-574-83067530




Mobile: +86-15867263600

Add: #102 65Building Dongying Xincun Ningbo City Zhejiang Province China

Fax: +86-574-87972399

E-mail: sales@jhswitch.com

Website: <http://www.jhswitch.com>

SPDT	Single pole, double throw	Two-way	Three-way	A simple changeover switch: C (COM, Common) is connected to L1 or to L2.	
DPST	Double pole, single throw	Double pole	Double pole	Equivalent to two SPST switches controlled by a single mechanism	
DPDT	Double pole, double throw			Equivalent to two SPDT switches controlled by a single mechanism.	

Description of JINGHAN SWITCH KCD1-101BL Series Rocker Switch

Types:	ON-OFF
Actuator :	Polycarbonate
Base :	Nylon(PA) 66
Contacts :	Silver plated Copper / Silver Alloyed
Movable Arm :	Tin-Plated Copper
Terminals :	Tin-Plated Copper
Ratings :	6A125V 10A250V
Dielectric Strength :	1500V for 1 Min
Insulation Resistance :	≥100MΩ
Contact Resistance :	≤30mΩ
Temperature Range :	-30~85℃
Life :	≥10000times
ROHS:	YES
CE:	YES
TUV:	YES